



Main Product Characteristics

BV_{DSS}	30V
$R_{DS(ON)}$	2.2mΩ
I_D	160A



PPAK5x6

Schematic Diagram

Features and Benefits

- Advanced MOSFET process technology
- Ideal for high efficiency switched mode power supplies
- Low on-resistance with low gate charge
- Fast switching and reverse body recovery



Description

The GSFP03160 utilizes the latest techniques to achieve high cell density and low on-resistance. These features make this device extremely efficient and reliable for use in high efficiency switch mode power supplies and a wide variety of other applications.

Absolute Maximum Ratings ($T_c=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Max.	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous ($T_c=25^\circ\text{C}$)	I_D	160	A
Drain Current-Continuous ($T_c=100^\circ\text{C}$)		102	
Drain Current-Pulsed ¹	I_{DM}	640	A
Single Pulse Avalanche Energy ²	E_{AS}	-	mJ
Single Pulse Avalanche Current ²	I_{AS}	-	A
Power Dissipation ($T_c=25^\circ\text{C}$)	P_D	115	W
Power Dissipation-Derate above 25°C		0.92	W/°C
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	62	°C/W
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	1.09	°C/W
Operating Junction Temperature Range	T_J	-55 To +150	°C
Storage Temperature Range	T_{STG}	-55 To +150	°C



GSFP03160

30V N-Channel MOSFET

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
On / Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	30	-	-	V
Drain-Source Leakage Current	I_{DSS}	$V_{\text{DS}}=27\text{V}, V_{\text{GS}}=0\text{V}, T_J=25^\circ\text{C}$	-	-	1	μA
		$V_{\text{DS}}=24\text{V}, V_{\text{GS}}=0\text{V}, T_J=85^\circ\text{C}$	-	-	10	μA
Gate-Source Leakage Current	I_{GSS}	$V_{\text{GS}}=20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	100	nA
Static Drain-Source On-Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=25\text{A}$	-	1.85	2.2	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}, I_{\text{D}}=20\text{A}$	-	2.5	3.3	
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}, I_{\text{D}}=250\mu\text{A}$	1.2	1.6	2.5	V
Dynamic and Switching Characteristics						
Total Gate Charge ^{3,4}	Q_g	$V_{\text{DS}}=15\text{V}, I_{\text{D}}=80\text{A}, V_{\text{GS}}=10\text{V}$	-	57	-	nC
Total Gate Charge ^{3,4}	Q_g	$V_{\text{DS}}=15\text{V}, I_{\text{D}}=80\text{A}, V_{\text{GS}}=4.5\text{V}$	-	28	-	
Gate-Source Charge ^{3,4}	Q_{gs}		-	6.6	-	
Gate-Drain Charge ^{3,4}	Q_{gd}		-	8	-	
Turn-On Delay Time ^{3,4}	$t_{\text{d}(\text{on})}$	$V_{\text{DD}}=15\text{V}, R_{\text{G}}=6\Omega, V_{\text{GS}}=10\text{V}, I_{\text{D}}=80\text{A}$	-	5	-	nS
Rise Time ^{3,4}	t_r		-	10	-	
Turn-Off Delay Time ^{3,4}	$t_{\text{d}(\text{off})}$		-	18	-	
Fall Time ^{3,4}	t_f		-	14	-	
Input Capacitance	C_{iss}	$V_{\text{DS}}=15\text{V}, V_{\text{GS}}=0\text{V}, F=1\text{MHz}$	-	3460	-	pF
Output Capacitance	C_{oss}		-	2300	-	
Reverse Transfer Capacitance	C_{rss}		-	45	-	
Gate Resistance	R_g	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\text{V}, F=1\text{MHz}$	-	1.5	-	Ω
Drain-Source Diode Characteristics and Maximum Ratings						
Continuous Source Current	I_s	$V_G=V_D=0\text{V},$ Force Current	-	-	160	A
Pulsed Source Current	I_{SM}	$V_{\text{GS}}=0\text{V}, I_{\text{s}}=1\text{A}, T_J=25^\circ\text{C}$	-	-	320	A
Diode Forward Voltage	V_{SD}		-	-	1	V

Note :

1. Repetitive rating: Pulsed width limited by maximum junction temperature.
2. $V_{\text{DD}}=25\text{V}, V_{\text{GS}}=10\text{V}, L=0.1\text{mH}, I_{\text{AS}}=-\text{A}, R_{\text{G}}=25\Omega$, starting $T_J=25^\circ\text{C}$.
3. Pulse test: pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.
4. Essentially independent of operating temperature.

Typical Electrical and Thermal Characteristic Curves




Figure 1. Continuous Drain Current vs. T_C




Figure 2. Normalized R_{DSON} vs. T_J




Figure 3. Normalized V_{th} vs. T_J




Figure 4. Gate Charge Waveform




Figure 5. Normalized Transient Impedance




Figure 6. Maximum Safe Operation Area

Typical Electrical and Thermal Characteristic Curves




Figure 7. Switching Time Waveform





Figure 8. Gate Charge Waveform

Package Outline Dimensions (PPAK5x6)



Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	0.850	1.200	0.031	0.047
b	0.300	0.510	0.012	0.020
C	0.200	0.300	0.008	0.012
D1	4.800	5.400	0.189	0.212
D2	3.610	4.310	0.142	0.170
E	5.850	6.300	0.230	0.248
E1	5.450	5.960	0.215	0.235
E2	3.300	3.920	0.130	0.154
e	1.270 BSC		0.050 BSC	
H	0.380	0.650	0.015	0.026
K	1.100	-	0.043	-
L	0.380	0.710	0.015	0.028
L1	0.050	0.250	0.002	0.009
θ	0°	12°	0°	12°