



Main Product Characteristics

$V_{(BR)DSS}$	100V
$R_{DS(ON)}$	11.8mΩ
I_D	55A



Features and Benefits

- Advanced MOSFET process technology
- Ideal for high efficiency switched mode power supplies
- Low on-resistance with low gate charge
- Fast switching and reverse body recovery

PPAK5X6

Schematic Diagram



Description

The GSFP1050 utilizes the latest techniques to achieve high cell density and low on-resistance. These features make this device extremely efficient and reliable for use in high efficiency switch mode power supply and a wide variety of other applications.

Absolute Maximum Ratings ($T_C=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Max.	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous ($T_C=25^\circ\text{C}$)	I_D	55	A
Drain Current-Continuous ($T_C=100^\circ\text{C}$)		35	
Drain Current-Pulsed ¹	I_{DM}	220	A
Single Pulse Avalanche Energy ²	E_{AS}	125	mJ
Single Pulse Avalanche Current ²	I_{AS}	50	A
Power Dissipation ($T_C=25^\circ\text{C}$)	P_D	98	W
Power Dissipation-Derate above 25°C		0.79	W/°C
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	62	°C/W
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	1.27	°C/W
Operating Junction Temperature Range	T_J	-55 To +150	°C
Storage Temperature Range	T_{STG}	-55 To +150	°C

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
On/Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=250\mu\text{A}$	100	-	-	V
Drain-Source Leakage Current	$I_{\text{DS}}^{\text{SS}}$	$V_{\text{DS}}=80\text{V}, V_{\text{GS}}=0\text{V}, T_J=25^\circ\text{C}$	-	-	1	μA
		$V_{\text{DS}}=80\text{V}, V_{\text{GS}}=0\text{V}, T_J=85^\circ\text{C}$	-	-	10	μA
Gate-Source Leakage Current	I_{GSS}	$V_{\text{GS}}=\pm 20\text{V}, V_{\text{DS}}=0\text{V}$	-	-	± 100	nA
Static Drain-Source On-Resistance ³	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=10\text{V}, I_{\text{D}}=20\text{A}$	-	9.8	11.8	$\text{m}\Omega$
		$V_{\text{GS}}=6\text{V}, I_{\text{D}}=15\text{A}$	-	14	18	
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}}=V_{\text{DS}}, I_{\text{D}}=250\mu\text{A}$	2	3	4	V
Forward Transconductance	g_{fs}	$V_{\text{DS}}=10\text{V}, I_{\text{D}}=3\text{A}$	-	8	-	S
Dynamic and Switching Characteristics						
Total Gate Charge ^{3,4}	Q_g	$V_{\text{DS}}=50\text{V}, I_{\text{D}}=30\text{A}, V_{\text{GS}}=10\text{V}$	-	15.4	23	nC
Gate-Source Charge ^{3,4}	Q_{gs}		-	3.9	6	
Gate-Drain Charge ^{3,4}	Q_{gd}		-	4.6	7	
Turn-On Delay Time ^{3,4}	$t_{\text{d}(\text{on})}$	$V_{\text{DD}}=50\text{V}, R_{\text{G}}=6\Omega, V_{\text{GS}}=10\text{V}, I_{\text{D}}=30\text{A}$	-	20	30	nS
Rise Time ^{3,4}	t_r		-	40	60	
Turn-Off Delay Time ^{3,4}	$t_{\text{d}(\text{off})}$		-	57	86	
Fall Time ^{3,4}	t_f		-	35	53	
Input Capacitance	C_{iss}	$V_{\text{DS}}=50\text{V}, V_{\text{GS}}=0\text{V}, F=1\text{MHz}$	-	1180	1750	pF
Output Capacitance	C_{oss}		-	250	375	
Reverse Transfer Capacitance	C_{rss}		-	2.2	4	
Gate Resistance	R_g	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\text{V}, F=1\text{MHz}$	-	1	-	Ω
Drain-Source Diode Characteristics and Maximum Ratings						
Continuous Source Current	I_s	$V_G=V_D=0\text{V}, \text{Force Current}$	-	-	55	A
Pulsed Source Current	I_{SM}		-	-	110	A
Diode Forward Voltage	V_{SD}	$V_{\text{GS}}=0\text{V}, I_{\text{s}}=1\text{A}, T_J=25^\circ\text{C}$	-	-	1	V
Reverse Recovery Time	t_{rr}	$V_R=100\text{V}, I_{\text{s}}=10\text{A}, \text{di/dt}=100\text{A}/\mu\text{s}, T_J=25^\circ\text{C}$	-	165	-	nS
Reverse Recovery Charge	Q_{rr}		-	265	-	nC

Note:

- Repetitive rating: Pulsed width limited by maximum junction temperature.
- $V_{\text{DD}}=50\text{V}, V_{\text{GS}}=10\text{V}, L=0.1\text{mH}, I_{\text{AS}}=50\text{A}, R_{\text{G}}=25\Omega, \text{starting } T_J=25^\circ\text{C}$.
- Pulse test: pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.
- Essentially independent of operation temperature.

Typical Electrical and Thermal Characteristic Curves




Figure 1. Typical Output Characteristics




Figure 2. Continuous Drain Current vs. T_C




Figure 3. Normalized $R_{DS(on)}$ vs. T_J




Figure 4. Normalized V_{th} vs. T_J




Figure 5. Turn-On Resistance vs. V_{GS}




Figure 6. Turn-On Resistance vs. I_D

Typical Electrical and Thermal Characteristic Curves




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9 . Normalized Transient Impedance




Figure 10. Maximum Safe Operation Area




Figure 11. Switching Time Waveform





Figure 12. EAS Waveform

Package Outline Dimensions

PPAK5X6



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	1.200	0.850	0.047	0.031
b	0.510	0.300	0.020	0.012
C	0.300	0.200	0.012	0.008
D1	5.400	4.800	0.212	0.189
D2	4.310	3.610	0.170	0.142
E	6.300	5.850	0.248	0.230
E1	5.960	5.450	0.235	0.215
E2	3.920	3.300	0.154	0.130
e	1.27BSC		0.05BSC	
H	0.650	0.380	0.026	0.015
K	-	1.100	-	0.043
L	0.710	0.380	0.028	0.015
L1	0.250	0.050	0.009	0.002
θ	12°	0°	12°	0°