



### Main Product Characteristics

$V_{(BR)DSS}$	150V
$R_{DS(ON)}$	52mΩ (Typ)
$I_D$	20A



### Features and Benefits

- Advanced MOSFET process technology
- Ideal for high efficiency switched mode power supplies
- Low on-resistance with low gate charge
- Fast switching and reverse body recovery



### Description

The GSFP68015 utilizes the latest techniques to achieve high cell density and low on-resistance. These features make this device extremely efficient and reliable for use in high efficiency switch mode power supplies and a wide variety of other applications.

### Absolute Maximum Ratings ( $T_C=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Max.	Unit
Drain-Source Voltage	$V_{DS}$	150	V
Gate-to-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current, @ Steady-State ( $T_C=25^\circ\text{C}$ ) <sup>1</sup>	$I_D$	20	A
Continuous Drain Current, @ Steady-State ( $T_C=100^\circ\text{C}$ )		14	A
Pulsed Drain Current <sup>2</sup>	$I_{DM}$	80	A
Power Dissipation ( $T_C=25^\circ\text{C}$ )	$P_D$	75	W
Linear Derating Factor ( $T_C=25^\circ\text{C}$ )		0.6	W/ $^\circ\text{C}$
Single Pulse Avalanche Energy <sup>3</sup>	$E_{AS}$	25	mJ
Junction-to-Case	$R_{JC}$	1.6	$^\circ\text{C}/\text{W}$
Junction-to-Ambient (PCB Mounted, Steady-State) <sup>4</sup>	$R_{JA}$	50	$^\circ\text{C}/\text{W}$
Operating Junction and Storage Temperature Range	$T_J/T_{STG}$	-55 to +150	$^\circ\text{C}$

**Electrical Characteristics** ( $T_A=25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
<b>On / Off Characteristics</b>						
Drain-to-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_D=250\mu\text{A}$	150	-	-	V
Drain-to-Source Leakage Current	$I_{\text{DSS}}$	$V_{\text{DS}}=150\text{V}, V_{\text{GS}}=0\text{V}$	-	-	1	$\mu\text{A}$
		$T_J=125^\circ\text{C}$	-	-	50	
Gate-to-Source Forward Leakage	$I_{\text{GSS}}$	$V_{\text{GS}}=20\text{V}$	-	-	100	$\text{nA}$
		$V_{\text{GS}}=-20\text{V}$	-	-	-100	
Static Drain-to-Source On-Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=10\text{V}, I_D=5\text{A}$	-	52	68	$\text{m}\Omega$
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}}=V_{\text{GS}}, I_D=250\mu\text{A}$	2.1	3	3.9	V
<b>Dynamic and Switching Characteristics</b>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=75\text{V}, f=1\text{MHz}$	-	518	-	$\text{pF}$
Output Capacitance	$C_{\text{oss}}$		-	76	-	
Reverse Transfer Capacitance	$C_{\text{rss}}$		-	3.3	-	
Total Gate Charge	$Q_g$	$I_D=5\text{A}, V_{\text{DS}}=75\text{V}, V_{\text{GS}}=10\text{V}$	-	9.1	-	$\text{nC}$
Gate-to-Source Charge	$Q_{\text{gs}}$		-	3.5	-	
Gate-to-Drain ("Miller") Charge	$Q_{\text{gd}}$		-	1.8	-	
Turn-On Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{GS}}=10\text{V}, V_{\text{DS}}=30\text{V}, I_D=5\text{A}, R_{\text{GEN}}=6\Omega$	-	7.3	-	$\text{nS}$
Rise Time	$t_r$		-	24	-	
Turn-Off Delay Time	$t_{\text{d}(\text{off})}$		-	14	-	
Fall Time	$t_f$		-	22	-	
Gate Resistance	$R_g$	$f=1\text{MHz}$	-	2.5	-	$\Omega$
<b>Source-Drain Ratings and Characteristics</b>						
Continuous Source Current (Body Diode)	$I_s$	MOSFET symbol showing the integral reverse p-n junction diode.	-	-	20	A
Pulsed Source Current (Body Diode)	$I_{\text{SM}}$		-	-	80	A
Diode Forward Voltage	$V_{\text{SD}}$	$I_s=2\text{A}, V_{\text{GS}}=0\text{V}$	1	-	1.2	V
Reverse Recovery Time	$T_{\text{rr}}$	$I_s=5\text{A}, V_{\text{GS}}=0\text{V}$ $dI/dt=100\text{A}/\mu\text{s}$	-	53	-	$\mu\text{s}$
Reverse Recovery Charge	$Q_{\text{rr}}$		-	0.11	-	nC

Notes

1. Pulse test: pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$ .
2. Repetitive rating; pulse width limited by max. junction temperature.
3.  $L=0.5\text{mH}$ ,  $R_G=25\Omega$ ,  $V_{\text{DD}}=50\text{V}$ ,  $I_{\text{AS}}=10\text{A}$ ,  $T_J=25^\circ\text{C}$ .
4. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.

## Typical Electrical and Thermal Characteristic Curves




Figure 1. Typical Output Characteristics




Figure 2. Transfer Characteristics




Figure 3.  $R_{DS(ON)}$  Vs. Drain Current




Figure 4. Body Diode Characteristics




Figure 5. Normalized  $BV_{DSS}$  Vs.  $T_J$




Figure 6. Gate Charge

### Typical Electrical and Thermal Characteristic Curves




Figure 7. Capacitance Characteristics





Figure 8. Normalized  $R_{DS(ON)}$  Vs.  $T_J$

### Package Outline Dimensions (PPAK5x6)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.200	0.035	0.047
c	0.154	0.354	0.006	0.014
D	4.800	5.400	0.189	0.213
E	5.660	6.060	0.223	0.239
D1	3.760	4.300	0.148	0.169
E1	5.900	6.350	0.232	0.250
b	0.300	0.550	0.012	0.022
k	1.100	1.500	0.043	0.059
e	1.070	1.370	0.042	0.054
E4	3.340	3.920	0.131	0.154
L	0.300	0.710	0.012	0.028
L1	-	0.120	-	0.005
H	0.400	0.710	0.016	0.028